



venoriainsaat.com

AFOAM- FFFP FOAMCONCENTRATE

Description

A FOAM-FFFP %1/3/6 is a film forming fluoroprotein foam concentrate contain hydrolysed protein and preservatives, together with a blend of fluorinated surfactants to achieve the maximum synergistic effect. The blend of fluorochemicals selected is effective in reducing the surface tension of water as well as the interfacial tension between water and oil sufficiently low to give stable film on the surface of the fuel and as a result it gives fire extinguishing rates superior to those obtained with synthetic based compounds.

TypicalPhysiochemicalProperties

Appearance	Brownliquid
pH(20 oC)	7± 1
Viscosity(20 oC)	min 5 cP
Density(20 oC)	1.03 ± 0.03 gr/cm3
Storage Temperature	Min -15° C ,Max+60 °C
Sediment(20 oC)	< %0,01
Recommended usage concentration	%1/3/6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	C
Fire Fight Performance Class	III
Pour Point	- 5°C
Freeze Point	-15°C

Application

A FOAM-FFFP %1/3/6 is used in high risk situations where hydrocarbons (such as diesel fuel, gasoline, crude oil) are stored, processed or transported A FOAM-FFFP %1/3/6 is designed and recommended for fast fire knockdown to save human lives, in addition to preventing catastrophic fire development; in particular when used in fire fighting vehicles in the airports and fixed fire systems in heliports. A FOAM-FFFP %1/3/6 can also be used as a wetting agent in combating fires in Class A materials such as paper, wood, tires. It is most suitable for simultaneous use with compatible powders in twin- agents or extinguishers. A FOAM-FFFP %1/3/6 is principally recommended for protection against fire in:

- Airports and heliports
- Aircraft hangars
- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Hydrocarbon storage tanks and power stations
- Mobile equipment
- Sprinkler Systems
- Loading Systems
- Marine Terminals and Vessels



Approvals, Listings, and Standards

A FOAM-FFFP %1/3/6 is in conformity with all national and international standards, EN 1568:2008 Part 1, Part 2, Part 3, 96/98/EC directives Aferm Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2008.

Foaming Properties

A FOAM-FFFP %1/3/6 Concentrate may be effectively applied using most conventional foam discharge equipment at %1/3/6 dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium. A FOAM-FFFP %1/3/6 Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices. Aspirating discharge devices typically produce expansion ratios from 3.5:1 to 10:1 depending on the type of device and the flow rate. Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

Performance

A FOAM-FFFP %1/3/6 is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Aferm Chemicals CO. Performance Laboratories.

Compatibility

A FOAM-FFFP %1/3/6 is suitable for use in combination with:
- Soft or hard, fresh or seawater.
- Dry powder extinguishing agents either separately or as twin agents systems.
- Expanded fluoroprotein foams for application to a fire in sequence or simultaneously.
A FOAM-FFFP %1/3/6 properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

A FOAM-FFFP %1/3/6 is exceptionally stable in long-term storage. Shelf life of 10 years can be expected if it is stored properly in original container A FOAM-FFFP %1/3/6 is suitable for storing steel tankbody.

Typical Packing Specification

Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight (kg)	1,0	1,2	9,0	70
Filled Weight(kg)	21	32	230	1075
Dimensions(mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

HFCMIX

EXPLANATION

HFCMIX consists of a new formula of volatile raw materials that can extinguish quickly. HFCMIX is effective in electrical fires, and when it is sprayed on the flame, it evacuates the oxygen in the environment and quickly extinguishes it. HFCMIX is non-corrosive, electrically non-conductive, clear-colorless and has low toxicity.

TECHNICAL SPECIFICATIONS

Appearance	Clear
pH (20 oC)	7-9
Viscosity (20 oC)	Min 2±2 cP
Density (20 oC)	1.6±0.3 gr/cm ³
Storage temperature	Min -15 °C, Max +60 °C.
Sediment (20 oC)	-
Application Amount	direct
Freeze Point	-15 °C

APPLICATION

It is suitable for use in HFCMIX tubes directly or in closed circuit systems. Since HFCMIX does not contain bromine and chlorine, it is an environmentally friendly product that does not harm the ozone layer.

Since extinguishing systems such as water, foam and chemical powder require cleaning and damage the extinguished equipment and equipment, HFCMIX is preferred as an alternative and more effective product.

Usage areas;

- Computer rooms & raised floors
- Museums, art galleries, libraries, buildings
- Process control rooms,
- Telecommunication facilities
- Money Cases,
- Archives,
- Laboratories etc.

COMPATIBILITY

HFCMIX is compatible with;

- Use with dry powder extinguishers
- Use with different types of fire extinguisher foams

If the HFCMIX is thawed after freezing, there will be no change in its performance.



PERFORMANCE

HFCMIX has a very effective extinguishing performance for electrical fires and its volatile feature is very successful. At the same time, it is effective in cooling the fire due to its special structure.

SAFETY AND HANDLING

You can request a 'Material Information Form' (MSDS) from AFMERKIMYA.

STORAGE

HFCMIX has an extremely stable structure. Since it has a volatile property, it is necessary to keep it closed. - Storage in its original packaging without opening - Preventing prolonged exposure to high temperatures shelf life is 10 years

PACKAGING FEATURES

CAPACITY	40 KG	300 KG	330 KG	1400 KG
	1.2	18	18	70
FULL WEIGHT (kg)	41.2	318	248	1470

SIZE (mm) 365x295x333 1200x800 1200x900

1200Lx1000Wx1165H

Barrels and drums can be palletized according to customer demand

BIO-FOAM

Description

BIO-FOAM is a special product that stops the fire quickly and blocs it for re-firing. Can be used at petroleum facilities, industrial and herbal oil fire sand all petroleum products like plastic. This product is harmless for the living, nature and atmosphere.

It is effective in fires, paper and wood .

Typical Physiochemical Properties

Appearance 20°C	Clear
pH(20°C)	7.1 ± 0.3
Viscosity(20°C)	100 ± 2cP
Density(20°C)	1.05 ± 0.05 gr/cm3
Storage Temperature	Min-15° C ,Max+60 °C
Surface Tension	≤ 40± 2 mN/m.
Sediment(20°C)	< %0,05
Storage Time (Year)	10
Recommended usage concentration	33%

Application

BIO-FOAM -is highly effective for fighting Class A & B fires without mixing water. This product is harmless fort helving, nature and atmosphere. BIO-FOAM has TURK-AK and ISO certificates. BIO-FOAM is a product with heavy viscosity and adhesive property which is used to extinguishing and blocking re-firing at shipyards, chemical factories, machine factories and petroleum companies.

Approvals, Listings, and Standards

BIO-FOAM is in conformity with all national and international standarts, TURK-AK and ISO certificates directives Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2008.

Storage

BIO-FOAM is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected If it is stored properly in original container.



Performance

BIO-FOAM is produced to rigorous quality control standarts. Ager each production, the performance tests are performed to product in Afmer Chemicals CO. PerformanceLaboratories.

Compatibility

BIO-FOAM is suitable for use in combination with :
- Soft or hard, fresh or seawater.

BIO-FOAM properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.
Although it does not have the ability to dry vegetation, it does not contain toxic substances.
It can be easily cleaned from the surface with water.
Biodegradable, no harm to the environment and human skin.
All kinds of dry chemical powder and all kinds of expanded foam at the same time or can be used repeatedly.
Foam concentrate can be mixed with all kinds of water

Typical Packing Specification

	Plastic Drum		Plastic Barrel	IBC Bulk
Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight (kg)	1.0	1.2	9.0	70
Filled Weight (kg)	21	32	230	1075
Dimensions (mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

AFOAM-SYNTHETIC 1-3-6%

Description

A FOAM-Synthetic % 1-3-6 Foam is specially formulated to make water more effective for fire fighting. The surfactants in A FOAM-Synthetic % 1-3-6 foam significantly reduce water's surface tension and, when mixed with air, create a superior foam blanket that surrounds fuels with a thick layer of water. This creates a barrier between the fuel and the fire, knocking down the fire faster than water alone, and allowing fire fighters to see the areas of application. Making the water more effective reduces the amount of water needed to extinguish the fire, reduces water damage and increases fire fighter safety through quicker knockdown and reduced mop-up/overhaul requirements.

Typical Physiochemical Properties

Appearance	liquid
pH(20 oC)	7.1 ± 1
Viscosity(20 oC)	Min. 7 cP
Density(20 oC)	1.03 ± 0.02 gr/cm ³
Storage Temperature	Min-15° C ,Max+60 °C
Surface Tension	35 ± 2 mN/m 'dir.
Sediment(20 oC)	< %0,05
Recommended usage concentration	%1-3-6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	C
Fire Fight Performance Class	III
Pour Point	-12°C
Freeze Point	-15°C

Application

A FOAM-Synthetic % 1-3-6 is highly effective for fighting Class A/B fires when mixed with water at use rates of % 1. It has proven effectiveness in many applications including Compressed Air Foam Systems (CAFS), structural firefighting, forest fire suppression and prescribed burning, mine fires, industrial Class A/B fires, and for extinguishing hydrocarbon spill fire



Approvals, Listings, and Standards

A FOAM-Synthetic % 1-3-6 is in conformity with all national and international standards, EN 1568:2008 Part 1, Part 2, Part 3, 96/98/EC directives Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Foaming Properties

A FOAM-Synthetic % 1-3-6 Concentrate may be effectively applied using most conventional foam discharge equipment at 1-3-6% dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

A FOAM-Synthetic % 1-3-6 Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices.

High-expansion : 200:1 - 500:1

Medium-expansion: 20:1-200:1

Low expansion: 10:1-20:1

Performance

A FOAM-Synthetic % 1-3-6 is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

A FOAM-Synthetic % 1-3-6 is suitable for use in combination with:

- Soft or hard, fresh or seawater.
- Dry powder extinguishing agents either separately or as twin agents systems.
- Expanded synthetic foams for application to a fire in sequence or simultaneously.

A FOAM-Synthetic properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

A FOAM-Synthetic % 1-3-6 is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container. A FOAM-Synthetic % 1-3-6 is suitable for storing steel tank body.

Typical Packing Specification

	Plastic Drum	Plastic Barrel	IBC Bulk
Capacity	20 litres	30 litres	200 litres
Empty Weight (kg)	1,0	1,2	9,0
Filled Weight (kg)	21	32	107,5
Dimensions (mm)	305 x 295 x 333	380 x 300 x 340	585 D x 945 H
			1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

A FOAM-FP 1-3-6% FoamConcentrate

Description

A FOAM-FP 1-3-6% is a protein foam concentrate contain hydrolysed protein and preservatives, together with a blend of surfactants to achieve the maximum synergistic effect. The blend of surfactants selected is effective in reducing the surface tension of water as well as the interfacial tension between water and oil sufficiently low to give stable film on the surface of the fuel and as a result it gives fire extinguishing rates superior to those obtained with synthetic based compounds.

TypicalPhysiochemicalProperties

Appearance	Clear Brown liquid
pH(20 oC)	7.1 ± 1
Viscosity(20 oC)	Min. 5
Density(20 oC)	1.03 ± 0.03 gr/cm ³
Storage Temperature	Min -15° C ,Max+60 °C
Sediment(20oC)	< %0,05
Recommended usage concentration	%1-3-6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	C
Fire Fight Performance Class	III
Pour Point	- 12°C
Freeze Point	-15°C

Application

A FOAM-FP 1-3-6% is used in high risk situations where hydrocarbons (such as diesel fuel, gasoline, crude oil) are stored, processed or transported A FOAM-FP 1-3-6% is designed and recommended for fast fire knockdown to save human lives, in addition to preventing catastrophic fire development; in particular when used in fire-fighting vehicles in the airports and fixed fire systems in heliports. A FOAM-FP 1-3-6% can also be used as a wetting agent in combating fires in Class A/B. It is most suitable for simultaneous use with compatible powders in twin-agents or extinguishers. A FOAM-FP 1-3-6% is principally recommended for protection against fire in:

- Airports and heliports
- Aircraft hangars
- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Hydrocarbon storage tanks and power stations
- Mobile equipment
- Sprinkler Systems
- Loading Systems
- Marine Terminals and Vessels



Approvals, Listings, and Standards

A FOAM-FP 1-3-6% is in conformity with all national and international standards, EN 1568:2018 Part 1, Part 2, Part 3, Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Foaming Properties

A FOAM-FP 1-3-6% Concentrate may be effectively applied using most conventional foam discharge equipment at 1% dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

A FOAM-FP 1-3-6% Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices.

Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

Performance

A FOAM-FP 1-3-6% is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

A FOAM-FP 1-3-6% is suitable for use in combination with:

- Soft or hard, fresh or seawater.
- Dry powder extinguishing agents either separately or as twin agents systems.
- Expanded FP foams for application to a fire in sequence or simultaneously.

A FOAM-FP 1-3-6% properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

A FOAM-FP 1-3-6% is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container. A FOAM-FP 1-3-6% is suitable for storing steel tankbody.

Typical Packing Specification

Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight (kg)	1,0	1,2	9,0	70
Filled Weight (kg)	21	32	230	1075
Dimensions (mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

CAFS FOAM %1-3-6

Description

CAFS FOAM % 1-3-6 Foam is specially formulated to make water more effective for fire fighting. The fluorosurfactants in CAFS FOAM % 1-3-6 foam significantly reduce water's surface tension and, when mixed with air, create a superior foam blanket that surrounds fuels with a thick layer of water. This creates a barrier between the fuel and the fire, knocking down the fire faster than water alone, and allowing fire fighters to see the areas of application. Making the water more effective reduces the amount of water needed to extinguish the fire, reduces water damage and increases fire fighter safety through quicker knockdown and reduced mop-up/overhaul requirements.

Typical Physicochemical Properties

Appearance	Pale yellow liquid
pH(20 oC)	7.5 ± 1
Viscosity(20 oC)	Min 10 cP
Density(20 oC)	1.05 ± 0.03 gr/cm3
Storage Temperature	Min-15° C ,Max+60° C
Sediment(20 oC)	< %0,05
Recommended usage concentration	%1-3-6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	B
Fire Fight Performance Class	III
Pour Point	-13°C
Freeze Point	-15°C

Application

CAFS FOAM % 1-3-6 is highly effective for fighting Class A/B fires when mixed with water at use rates of % 1-3-6. It has proven effectiveness in many applications including Compressed Air Foam Systems (CAFS), structural firefighting, forest fire suppression and prescribed burning, mine fires, industrial Class A/B fires, and for extinguishing hydrocarbon spill fire



Approvals, Listings, and Standards

CAFS FOAM % 1-3-6 is in conformity with all national and international standards, EN 1568:2018 Part 1, Part 2, Part 3 Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Foaming Properties

CAFS FOAM % 1-3-6 Concentrate may be effectively applied using most conventional foam discharge equipment at %1-3-6. dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

CAFS FOAM % 1-3-6 Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices.

Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 200:1 to 500:1.

Performance

CAFS FOAM %1-3-6 is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

CAFS FOAM % 1-3-6 is suitable for use in combination with:

- Soft or hard, fresh or seawater.
- Dry powder extinguishing agents either separately or as twin agents systems.
- Expanded CAFS foams for application to a fire in sequence or simultaneously.

CAFS FOAM % 1-3-6 properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

CAFS FOAM % 1-3-6 is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container CAFS FOAM % 1-3-6 is suitable for storing steel tank body.

Typical Packing Specification

Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight (kg)	1,0	1,2	9,0	70
Filled Weight (kg)	21	32	230	1075
Dimensions (mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

A FOAM-AR 1-3-6% AFFF AR FoamConcentrate

Description

A FOAM-1-3-6AR (Alcohol Resistant Aqueous Film-Forming Foam) concentrates are high-performance, firefighting AR-AFFF concentrates formulated with hydrocarbon and fluorosurfactants, fluoropolymers and water-soluble polysaccharide polymers. When A FOAM-1-3-6AR is applied to a water-soluble fuel, a polymeric membrane is formed between the foam and the fuel.

When the foam is applied to a hydrocarbon fuel, a film is created at the fuel/air interface, similar to AFFF. Also like AFFF, AR-AFFF inhibits vapor release and provides a foam blanket cooling effect in the suppression of both types of Class B fires.

TypicalPhysiochemicalProperties

Appearance	Pale Yellow liquid
pH(20 oC)	7.2 ± 1
Viscosity(20 oC)	Min 300 cP
Density(20 oC)	1.03 ± 0.01 gr/cm3
Storage Temperature	Min-15° C ,Max+60 °C
Surface Tension	19 ± 2 mN/m'dir.
Sediment(20 oC)	< % 0,05
Recommended usage concentration	%1-3-6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	C
Fire Fight Performance Class	III
Freeze Point	-15°C

Application

A FOAM-1-3-6AR concentrates produce foams that are effective in suppressing both types of Class B fuel fires – polar solvent (water soluble) fuels such as methanol, ethanol and acetone, as well as hydrocarbon fuels, such as gasoline, diesel and petroleum.

A FOAM-1-3-6AR is principally recommended for protection against fire in:

- Fuel or chemical storage tanks
- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Docks and on-board marine systems
- Mobile equipment



Approvals, Listings, and Standards

A FOAM-1-3-6AR is in conformity with all national and international standards, EN 1568:2018 Part 1, Part 2, Part 3, Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Foaming Properties

A FOAM-1-3-6AR Concentrate may be effectively applied using most conventional foam discharge equipment at 1-3-6% dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

A FOAM-1-3-6AR Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices.

Aspirating discharge devices typically produce expansion ratios from 3.5:1 to 10:1 depending on the type of device and the flow rate. Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

Performance

A FOAM-1-3-6AR is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

A FOAM-1-3-6AR is suitable for use in combination with:

- Soft or hard, fresh or seawater.
- Dry powder extinguishing agents either separately or as twin agents systems.
- Expanded AFFF-AR foams for application to a fire in sequence or simultaneously.

A FOAM-1-3-6AR properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

A FOAM-1-3-6AR is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container. A FOAM-1-3-6AR is suitable for storing steel tankbody.

TypicalPackingSpecification

Capacity	20 litree	30 litree	220 litree	1000 litree
Empty Weight(kg)	1.0	1.2	9.0	78
Filled Weight(kg)	21	32	230	1075
Dimensions(mm)	305 x 295 x 332	380 x 300 x 360	565 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

AFOAMF AFFF %1-3-6 FoamConcentrate

Description

A FOAM-%1-3-6 AFFF (Aqueous Film-Forming Foam) Concentrate combines fluoro- and hydrocarbon-surfactant technologies to provide superior fire and vapor suppression for Class B hydrocarbon fuel fires. This AFFF foam concentrate is intended for fire fighting applications at 1-3-6% solution in fresh, salt, or hard water.

A FOAM- %1-3-6 AFFF foam solution utilizes three suppression mechanisms intended for rapid fire knockdown and superior burnback resistance:

The foam blanket blocks oxygen supply to the fuel.

Liquid drains from the foam blanket and forms an aqueous film that suppresses fuel vapor and seals the fuel surface.

The water content of the foam solution produces a cooling effect for additional fire suppression.

TypicalPhysiochemicalProperties

Appearance	Pale yellow liquid
pH(20 oC)	7.2 ± 1
Viscosity(20 oC)	Min. 3.0 cP
Density(20 oC)	1.02 ± 0.02 gr/cm3
Storage Temperature	Min-15° C ,Max+60 °C
Surface Tension	19 ± 1 mN/m'dir.
Sediment(20 oC)	< % 0,0
Recommended usage concentration	%1-3-6
Suitable for use with fresh or seawater.	
Burn-Back Resistance Level	C
Fire Fight Performance Class	III
Freeze Point	-15°C

Application

A FOAM- %1-3-6 AFFF is used in high risk situations where hydrocarbons (such as diesel fuel, gasoline, crude oil) are stored, processed or transported.

A FOAM- %1-3-6 AFFF is designed and recommended for fast fire knockdown to save human lives, in addition to preventing catastrophic fire development; in particular when used in firefighting vehicles in the airports and fixed fire systems in heliports.

A FOAM- %1-3-6 AFFF can also be used as a wetting agent in combating A FOAM-1F Class A materials such as paper, wood, tires. It is most suitable for simultaneous use with compatible powders in twin-agents or extinguishers.

A FOAM- %1-3-6 AFFF is principally recommended for protection against fire in:

- Airports and heliports
- Aircraft hangars
- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Hydrocarbon storage tanks and power stations
- Mobile equipment
- Sprinkler Systems
- Loading Systems
- Marine Terminals and Vessels



Approvals, Listings, and Standards

A FOAM- %1-3-6 AFFF is in conformity with all national and international standards, EN 1568:2018 Part 1, Part 2, Part 3 directives Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Foaming Properties

A FOAM- %1-3-6 AFFF Concentrate may be effectively applied using most conventional foam discharge equipment at 1-3-6% dilution with fresh, salt, or hard water. A FOAM- %1-3-6 AFFF Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices. Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Aspirating low-expansion discharge devices typically produce expansion ratios from 3.5:1 to 10:1, depending on the type of device and the flow rate. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

Performance

A FOAM- %1-3-6 AFFF is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

A FOAM- %1-3-6 AFFF is suitable for use in combination with:

- Soft or hard, fresh or seawater.
 - Dry powder extinguishing agents either separately or as twin agent systems.
 - Expanded AFFF foams for application to a fire in sequence or simultaneously.
- A FOAM- %1-3-6 AFFF properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Storage

A FOAM- %1-3-6 AFFF is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container. A FOAM- %1-3-6 AFFF is suitable for storing steel tank body.

TypicalPacking Specification

	Plastic Drum		Plastic Barrel	IBC Safe
Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight(kg)	1.0	1.2	5.0	70
Filled Weight(kg)	21	32	230	1070
Dimensions(mm)	305 x 295 x 335	380 x 300 x 300	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

LIQUID POTASSIUM for F TYPE FIRE

Description

Generally used at restaurants for Paddle box fire systems. It is very effective for oil fryers, grill and fat burns at cookers. It is an ecological product that harmless to human health than environment. It provides excellent cooling and stops re-fire again. Easily cleanable after fire.

Typical Physiochemical Properties

Appearance 20°C	clear-looking and yellow
pH(20°C)	9 ± 0.3
Viscosity(20°C)	5 ± 0.1 cP
Density(20°C)	1.00 ± 0.05 gr/cm ³
Storage Temperature	Min-10° C ,Max+50 °C
Surface Tension	≤ 48 mN/m
Sediment(20°C)	< %0,05
Storage Time (Year)	10

Application

LIQUID POTASSIUM is also vital for the personnel, as the place where the fire is most likely to be started is the kitchens that are the center of the work done by the fire. As long as the kitchen and oven are used, the things that are created by the fumes going upwards start to present danger. It is very easy to ignite the remains in the constantly warming pit. This is where the LIQUID POTASSIUM enters and extinguishes without starting to extinguish. In such fires, the flames rising upward or igniting the roof directly cause the kitchen staff to be unaware and the danger suddenly grows. LIQUID POTASSIUM is not concentrated, it is used directly, and it is suitable for use in the kitchen thanks to the organic ingredients in its structure.

Approvals, Listings, and Standards

LIQUID POTASSIUM is in conformity with all national and international standards, TURK-AK and ISO certificates directives Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2015.

Storage

LIQUID POTASSIUM is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container.



Performance

LIQUID POTASSIUM is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

LIQUID POTASSIUM properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Although it does not have the ability to dry vegetation, it does not contain toxic substances.

It can be easily cleaned from the surface with water.

Biodegradable, no harm to the environment and human skin.

All kinds of dry chemical powder and all kinds of expanded foam at the same time or can be used repeatedly.

Typical Packing Specification

	Plastic Drum	Plastic Barrel	IBC Bulk
Capacity	20 litres	30 litres	220 litres
Empty Weight (kg)	1,0	1,2	9,0
Filled Weight (kg)	21	32	107,5
Dimensions (mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H
			1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

PRO -JEL

Description

PRO- JEL provides high efficiency with low supply. The cooling performance of the product is excellent and stops re-firing. This product is harmless for helving, nature and atmosphere. Pro-Gel has TURK-AK and ISO certificates. Pro-Gel is a product with heavy viscosity and adhesive property which is used to extinguishing and blocking re-firing at shipyards, chemical factories, machine factories and petroleum companies. Used without mixing with water. Pro -Jel it can be used for all Class A and B fires.

Typical Physiochemical Properties

Appearance 20°C	Clear
pH(20°C)	7.2 ± 0.3
Viscosity(20°C)	Min 900 cP
Density(20°C)	1.01 ± 0.01 gr/cm3
Storage Temperature	Min-5° C ,Max+50 °C
Surface Tension	39 ± 2 mN/m.
Sediment(20°C)	< %0,05
Storage Time (Year)	10

Application

PRO - JEL -is highly effective for fighting Class A & B fires without mixing water. This product is harmless for helving, nature and atmosphere. Pro-Gel has TURK-AK and ISO certificates. Pro-Gel is a product with heavy viscosity and adhesive property which is used to extinguishing and blocking re-firing at shipyards, chemical factories, machine factories and petroleum companies.

Approvals, Listings, and Standards

PRO JEL is in conformity with all national and international standards, TURK-AK and ISO certificates directives Afmer Chemicals CO. operates a quality management system which complies with requirements of ISO 9001:2008.

Storage

PRO- JEL is exceptionally stable in long-term storage. Shelf life of at 10 years can be expected if it is stored properly in original container.



Performance

PRO JEL is produced to rigorous quality control standards. After each production, the performance tests are performed to product in Afmer Chemicals CO. Performance Laboratories.

Compatibility

PRO JEL is NOT suitable for use in combination with:
- Soft or hard, fresh or seawater.

PRO JEL properties do not change in case of frost. It recovers its initial properties as soon as it is defrosted.

Although it does not have the ability to dry vegetation, it does not contain toxic substances.

It can be easily cleaned from the surface with water.

Biodegradable, no harm to the environment and human skin.

All kinds of dry chemical powder and all kinds of expanded foam at the same time or can be used repeatedly.

Typical Packing Specification

	Plastic Drum		Plastic Barrel	IBC Bulk
Capacity	20 litres	30 litres	220 litres	1000 litres
Empty Weight (kg)	1,0	1,2	9,0	70
Filled Weight (kg)	21	32	230	1075
Dimensions (mm)	305 x 295 x 333	380 x 300 x 360	585 D x 945 H	1200 L x 1000 W x 1165 H

Palletizing of pails and drums is available upon request.

APLUS RETERDANT CONCENTRATE

DESCRIPTION

In forest and land areas, in addition to the extinguishers required for fire fighting, Retardants are used to prevent the spread of fire.

Serious precautions can be taken by squeezing the Retardants into areas with high hazard and potential. A PLUSRETERDANT produced for this purpose provides a very long-term protection thanks to the inorganic salt compounds and corrosive inhibitors in its structure. The water in its content acts as a carrier component that enables APLUSRETERDANT to reach large areas. At the same time, thanks to the polymer chains in its content, it quickly falls to the ground when sprayed from the air, and thanks to these elastic chains, it adheres to the plant surfaces and prevents evaporation, taking the protection to the highest level.

TECHNICAL SPECIFICATIONS

Appearance	Clear
pH(20°C)	7.4±0.5
Viscosity(20 °C)	200 cP
Density(20°C)	1.4±2gr/cm3
Storage Temperature	Min-10°C,Max+60°C
Sediment(20°C)	<%0,05
Recommended usage concentration	~%15
Can be used with sea and tap water	
Freezing Point	-10

APPLICATION

APLUSRETERDANT is applied with helicopter or rotor blade aircraft. APLUSRETERDANT is also applied from the ground in order to take precautions for fires foreseen in at-risk environments. APLUSRETERDANT is a liquid concentrate that can be easily mixed with water through proportioning systems and is easy to use. APLUSRETERDANT low and medium viscosity available. Medium viscosity is ideal for higher altitude drops or where higher coverage levels are desired. APLUSRETERDANT retardants are used in forest, bush or grassland areas for control. The product, which is blue in color, provides significant convenience for both pilots and firefighters to easily distinguish the area applied.

COMPATIBILITY

APLUSRETERDANT - It is suitable to use with seawater at the specified application rates.

If APLUSRETERDANT foam concentrate is thawed after freezing, its performance will not change.



TOXICITY

APLUSRETERDANT does not harm the growth of trees, plants and herbs, and supports the development of plants and soil fertility thanks to its beneficial components. Therefore, APLUSRETERDANT is an environmentally friendly ecological product.

PERFORMANCE

Prevention of fire retardants in high-risk areas, could potentially stop most wildfires. To prevent these high-risk areas from igniting throughout the season, APLUSRETERDANT has been developed with better adhesion and evenness on vegetation. Thanks to this feature, it delays the ignition and reduces the combustion rate to a large extent.

SAFETY AND HANDLING

You can request a 'Material Information Form' (MSDS) from AFMERKIMYA.

STORAGE

APLUSRETERDANT concentrate has an extremely stable structure. Keeping it in its original packaging without opening. Avoid prolonged exposure to high temperatures. Shelf life is 10 years.

PACKAGING FEATURES

Capacity	20 KG	30 KG	220 KG	1000 KG
Empty Weight(kg)	1.0	1.2	9.0	70
FULL WEIGHT(kg)	21	32	230	1075
DIMENSIONS(mm)	305x295x333	380x300x360	585Dx945H	1200Lx1000Wx1165H

Barrels and drums can be palletized according to customer demand.



: VENORIAO@GMAIL.COM



: AHMAD BENSHI



: İSTANBUL/TÜRKİYE



: 0 506 060 91 42